



The Quite OK Image Format Specification

Version 1.0, 2021.12.21 – qoiformat.org – Dominic Szablewski

A QOI file consists of a 14-byte header, followed by any number of data “chunks” and an 8-byte end marker.

```

qoi_header {
    char    magic[4]; // magic bytes "qoif"
    uint32_t width; // image width in pixels (BE)
    uint32_t height; // image height in pixels (BE)
    uint8_t channels; // 3 = RGB, 4 = RGBA
    uint8_t colorspace; // 0 = sRGB with linear alpha
                    // 1 = all channels linear
};

```

The colorspace and channel fields are purely informative. They do not change the behavior of the en-/decoder.

Images are encoded row by row, left to right, top to bottom. The decoder and encoder start with {r: 0, g: 0, b: 0, a: 255} as the previous pixel value. An image is complete when all pixels specified by width * height have been covered. Pixels are encoded as:

- a run of the previous pixel
- an index into an array of previously seen pixels
- a difference to the previous pixel value in r,g,b
- full r,g,b or r,g,b,a values

The color channels are assumed to not be pre-multiplied with the alpha channel (“un-premultiplied alpha”).

A running array[64] (zero-initialized) of previously seen pixel values is maintained by the encoder and decoder. Each pixel that is seen by the encoder and decoder is put into this array at the position formed by a hash function of the color value. In the encoder, if the pixel value at the index matches the current pixel, this index position is written to the stream as QOI_OP_INDEX. The hash function for the index is:

$$\text{index_position} = (r * 3 + g * 5 + b * 7 + a * 11) \% 64$$

Each chunk starts with a 2- or 8-bit tag, followed by a number of data bits. The bit length of chunks is divisible by 8 - i.e. all chunks are byte aligned. All values encoded in these data bits have the most significant bit on the left. The 8-bit tags have precedence over the 2-bit tags. A decoder must check for the presence of an 8-bit tag first.

The byte stream's end is marked with 7 0x00 bytes followed by a single 0x01 byte.

The possible chunks are:

QOI_OP_RGB												
Byte[0]								Byte[1]	Byte[2]	Byte[3]		
7	6	5	4	3	2	1	0	7 .. 0	7 .. 0	7 .. 0		
1	1	1	1	1	1	1	0	red	green	blue		

- 8-bit tag b11111110
- 8-bit red channel value
- 8-bit green channel value
- 8-bit blue channel value

The alpha value remains unchanged from the previous pixel.

QOI_OP_RGBA																
Byte[0]								Byte[1]	Byte[2]	Byte[3]	Byte[4]					
7	6	5	4	3	2	1	0	7 .. 0	7 .. 0	7 .. 0	7 .. 0					
1	1	1	1	1	1	1	1	red	green	blue	alpha					

- 8-bit tag b11111111
- 8-bit red channel value
- 8-bit green channel value
- 8-bit blue channel value
- 8-bit alpha channel value

QOI_OP_INDEX							
Byte[0]							
7	6	5	4	3	2	1	0
0	0	index					

- 2-bit tag b00
- 6-bit index into the color index array: 0..63

A valid encoder must not issue 7 or more consecutive QOI_OP_INDEX chunks to the index 0, to avoid confusion with the end marker.

QOI_OP_DIFF									
Byte[0]									
7	6	5	4	3	2	1	0		
0	1	dr	dg	db					

- 2-bit tag b01
- 2-bit red channel difference from the previous pixel -2..1
- 2-bit green channel difference from the previous pixel -2..1
- 2-bit blue channel difference from the previous pixel -2..1

The difference to the current channel values are using a wraparound operation, so 1 - 2 will result in 255, while 255 + 1 will result in 0.

Values are stored as unsigned integers with a bias of 2. E.g. -2 is stored as 0 (b00). 1 is stored as 3 (b11).

The alpha value remains unchanged from the previous pixel.

QOI_OP_LUMA															
Byte[0]							Byte[1]								
7	6	5	4	3	2	1	0	7	6	5	4	3	2	1	0
1	0	diff green					dr - dg			db - dg					

- 2-bit tag b10
- 6-bit green channel difference from the previous pixel -32..31
- 4-bit red channel difference minus green channel difference -8..7
- 4-bit blue channel difference minus green channel difference -8..7

The green channel is used to indicate the general direction of change and is encoded in 6 bits. The red and blue channels (dr and db) base their diffs off of the green channel difference. I.e.:

$$\begin{aligned} \text{dr_dg} &= (\text{last_px.r} - \text{cur_px.r}) - (\text{last_px.g} - \text{cur_px.g}) \\ \text{db_dg} &= (\text{last_px.b} - \text{cur_px.b}) - (\text{last_px.g} - \text{cur_px.g}) \end{aligned}$$

The difference to the current channel values are using a wraparound operation, so 10 - 13 will result in 253, while 250 + 7 will result in 1.

Values are stored as unsigned integers with a bias of 32 for the green channel and a bias of 8 for the red and blue channel.

The alpha value remains unchanged from the previous pixel.

QOI_OP_RUN							
Byte[0]							
7	6	5	4	3	2	1	0
1	1	run					

- 2-bit tag b11
- 6-bit run-length repeating the previous pixel: 1..62

The run-length is stored with a bias of -1. Note that the run-lengths 63 and 64 (b111110 and b111111) are illegal as they are occupied by the QOI_OP_RGB and QOI_OP_RGBA tags.